



EW-7722PnD

N600 Wireless Dual-Band PCI Express Adapter



The Edimax EW-7722PnD N600 Wireless Dual-Band PCI Express Adapter is specifically designed to add highspeed, dual-band (2.4GHz/5GHz) wireless connectivity to your desktop computer. Designed with 802.11a/b/g/n standards, 2T2R MIMO technology, and two detachable 2dBi dual-band antennas, this wireless PCI Express adapter allows for fast and stable wireless networking with data rates up to 300Mbps on the 2.4GHz or 5GHz band. It can be easily set up with the bundled EZmax multi-language setup wizard, and comes with a low-profile bracket for installation on small computers.

300Mbps (2.4GHz) or 300Mbps (5GHz) Max. Wi-Fi Speed

With 2T2R MIMO technology, this Edimax dual-band wireless adapter is able to establish super fast Wi-Fi connections with either 2.4GHz or 5GHz wireless devices. Designed in compliance with 802.11a/b/g/n standards, this dual-band wireless adapter can reach maximum Wi-Fi speeds of 300Mbps on either the 2.4GHz or the 5GHz band.

First-Class Reliability

The EW-7722PnD's exceptional chipset offers increased bandwidth and more functionality than other PCI network adapters. This adapter is specifically designed to utilize the full bandwidth capacity of the PCI Express bus, thus eliminating collisions and latencies that exist with current 32-bit and 64-bit PCI bus architectures.

Detachable 3dBi Dual-Band Antennas for Improved Wireless Performance

The EW-7722PnD comes with two detachable 3dBi dual-band antennas, which enable it to achieve better signal quality compared to common wireless adapters. The antennas' detachable design also gives users the flexibility of using the antennas with extension cables for optimal antenna placement.





FEATURES & TECHNICAL SPECIFICATIONS

- Complies with 802.11a/b/g/n wireless standards
- 2.4GHz/5GHz dual-band wireless connectivity
- Wireless data rates up to 300Mbps (2.4GHz) or 300Mbps (5GHz)
- Features EZmax multi-language setup wizard
- Features a hardware WPS (Wi-Fi Protected Setup) button
- Includes a low-profile bracket for small computers

Interfaces	Output Power	Data Rates
 1 x PCI Express interface 1 x Link LED 1 x Tx/Rx LED 1 x WPS button 2 x RP-SMA connector 2 x detachable 3dBi dual-band antenna 	2.4GHz *11b: 17dBm±1.5 *11g: 14dBm±1.5 *11n: 13dBm±1.5 (20/40MHz) 5GHz *11a: 13dBm±1.5 *11n: 13dBm±1.5 (20/40MHz)	 #11a: 6/9/12/24/36/48/54Mbps #11b: 1/2/5.5/11Mbps #11g: 6/9/12/24/36/48/54Mbps #11n (20MHz): MCS0-15 (up to 144Mbps) #11n (40MHz): MCS0-15 (up to 300Mbps)
Frequency Band	Standards	Temperature
 2.4000 to 2.4835GHz (Industrial Scientific Medical Band) 5.150 to 5.825Ghz (subject to local regulations) 	 IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n 	♦Operating: 32 - 103°F (0-40°C) ♦Storage: -4 - 149°F (-20 - 65°C)
Wireless Security	Installation	Humidity
<pre>#64/128-bit WEP, WPA, WPA2 #WPS configuration</pre>	Multi-language EZmax Setup Wizard	Operating: 10 - 90% (non-condensing) Storage: max. 95% (non-condensing)
System Requirements	Dimensions	Certifications
Windows XP/Vista/7	◆22 x 121 x 88 mm (without antenna)	

NETWORK SETUP DIAGRAM AND RELATED PRODUCTS

• Install the EW-7722PnD wireless adapter on your computer

• Set it up with the multi-language EZmax wizard

• Connect it to an 802.11a/b/g/n wireless access point or router



Copyright © 2012 Edimax Technology Co. Ltd. All rights reserved. Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.